## FIRST-TIME INSTALLATION OF CABIN AIR FILTER PC9957x

Access Door – OE#22759208

Cabin Air Filter – OE#22759203, 23101674

APPLICATIONS					
YEAR	MAKE, MODEL	ENGINE	YEAR	MAKE, MODEL	ENGINE
2007 - 2014	Cadillac Escalade	6.0L, 6.2L	2007 - 2014	Chevrolet Silverado 2500	4.8L, 5.3L
2007 - 2014	Cadillac Escalade ESV	6.2L	2007 - 2013	Chevrolet Silverado 3500	5.7L, 6.0L
2007 - 2013	Cadillac Escalade EXT	6.2L	2007 - 2014	Chevrolet Suburban 1500, 2500	5.3L, 6.0L
2007 - 2013	Chevrolet Avalanche	5.3L	2007 - 2014	Chevrolet Tahoe, GMC Yukon, Yukon XL 1500, Yukon XL	4.8L, 5.3L, 6.0L, 6.2L
2007 - 2009	Chevrolet Avalanche	6.0L	2007 - 2014	Chevrolet Silverado 2500HD, Silverado 3500HD, GMC Sierra 2500HD, Sierra 3500HD	6.0L, 6.6L
2007 - 2013	Chevrolet Silverado 1500, GMC Sierra 1500	4.3L, 4.8L, 5.3L, 6.0L, 6.2L			

The applications listed on the product page do not come with a factory installed cabin air filter. However, it can be retrofitted. It requires cutting the opening of the access panel to accept the filter. An access door is then included which conceals the opening.

- 1. Locate and remove the screws holding the right-side lower insulator panel.
- On the underside of the HVAC case, inboard of the blower motor, locate the groove (2) around the molded-in cabin air filter access panel (1) as shown in the illustration.
- Carefully cut out the molded-in cabin air filter access panel using a suitable tool. Always keep the tool inside the groove. Note: The size of the opening is 10.25" x 1" (260.3 mm x 25.4 mm).
- 4. Once the molded-in cabin filter access panel is removed, ensure the opening is free of burrs and debris.
- Bend the top stage and slowly insert the cabin air filter into the HVAC module, with the filter stages (cut outs) facing inboard while the pull strip is pointed down.
- 6. The cabin air filter MUST be flush with the HVAC module access opening.
- 7. Install the cabin air filter access door hook onto the slot in the HVAC module and press the cover flush while installing the fastener.



8. Tighten the fastener to 1.6 N.m (14 lb in)